

Sticker & Decal Installation Instructions

Follow these instructions to insure that your stickers and decals are properly installed.

Surface preparation:

1. The surface to which you will be applying the decal needs to be clean and dry. Rubbing alcohol is a good cleaner, but you need to test to make sure the surface you're cleaning can handle alcohol based cleaners. If you can't use rubbing alcohol, use a mild cleaner and be sure to completely rinse the surface.
2. You need to have a temperature of +/- 50 degrees F to insure the adhesive will adhere properly.

Choose an installation option:

1. Dry installation can be used for any size decal, but the wet installation method is more forgiving and may be a better choice for those with limited installation experience and a large (>12"x12") decal.
2. For wet installation:
 - a. Fill a small spray bottle with water, add about a teaspoon of liquid dish soap, and mix well.
 - b. Remove the backing paper from the decal.
 - c. Spray both the back side of the decal and the surface you will be installing on with the water soap solution.
 - d. Lightly place the decal and arrange until it's positioned exactly where you want it.
 - e. With a squeegee (side of a credit card works fine) and working from the center to edges, press the decal on to the surface and squeeze the water out.
 - f. Squeegee the entire surface of the decal, always working from the center to the edges.
 - g. Remove the application tape from the top of your decal.
3. For dry installation:
 - a. Position the decal where you want it.
 - b. Tape the decal in place by running a piece of masking tape over the middle of the decal to hold it in position on the surface.
 - c. Lift one side of the decal and carefully remove the backing paper from 1/2 of the decal. Cut the backing paper off to get it out of your way.

- d. Working from the center (taped) area of the decal, squeegee the decal in place.
- e. Remove masking tape and backing paper from other side of the decal and repeat the squeegee process.
- f. Carefully remove the application tape from the top of the decal.

Care of your stickers & decals:

1. If you have any bubbles in the decal, use a pin to pop them and press the air out.
2. If installing on a vehicle, wait at least 1 week before running the vehicle through an automated car wash or exposing to any high pressure washing. For longest life, never apply pressure washing wand to decal area at close range as the combination of very high pressure and hot water could cause the decal to lift.
3. To remove your stickers or decals: Use a blow dryer to heat the decal adhesive, and pull the decal off. Be careful not to use any tools to peel decals that scratch the surface where the decals are installed.